

8 Flexible Hoses



Non-aggressive liquids

Waste water, Industrial liquids, General fluids



- Flex SuperElastično

W8P22

Osobine

Visokokvalitetno PVC crevo sa krutom PVC spiralom do prečnika 51mm, veći prečnici sa kružnom spiralom, nudeći izuzetno fleksibilno crevo i pri hladnim uslovima.

Primena

Kod pražnjenja/usisavanja u primeni za industrijsku vodu, đubriva...

Izrada

PCV, siva sa plavom spiralom, glatka unutrašnjost, korugovano spolja



Vakum: 0.9 bar **Opseg Temperature:** -25°C / +60°C **Radijus savijanja:** 3.5x inside diameter



Tehnički podaci

Šifra	iØ	eØ	Visina	Težina	Debljina zidova	Pritisak Max Radni	Dužina
	mm	mm	mm	g/mt	mm	bar	mt (max)
W8P22025	25	33	7.5	400	4.2	7.0	50
W8P22030	30		8.0				
W8P22032	32	41	8.0	540	4.7	6.0	50
W8P22035	35		8.5				
W8P22038	38	47	8.5	650	4.7	6.0	
W8P22040	40		8.5				
W8P22045	45		8.5				
W8P22051	51	62	9.5	950	5.7	5.0	50
W8P22055	55		10.0				
W8P22060	60						
W8P22063	63	74	10.25	1130	5.7	4.5	50
W8P22065	65						
W8P22070	70		10.5				
W8P22076	76	88	11.0	1600	6.0	4.0	50
W8P22080	80	93	11.0	1700	6.4	4.0	50
W8P22090	90	103	12.0	1850	6.4	3.5	50
W8P22102	102	115	13.0	2200	6.7	3.0	50
W8P22110	110	124	13.0	2400	7.0	3.0	30
W8P22120	120	134	13.0	2700	7.0	3.0	30
W8P22127	127	143	15.0	3100	8.0	2.5	30
W8P22152	152	170	15.5	4200	9.0	2.0	30
W8P22203	203	228	20.0	7800	12.5	1.5	30

ATAG reserves the right to make changes without notice, by virtue of any quality improvements and/or product specifications

— src.: 000H

20128 MILANO
V.le Monza, 274

Tel.: +39 02 2552251 - Fax: +39 02 2575289
e-mail: ufftec@atag.it

40138 BOLOGNA
Via E. Mattei, 84/21

Tel.: +39 051 6010077 - Fax: +39 051 538590
e-mail: infobologna@atag.it

36065 Mussolente (vi)
Via Giovanni Pascoli, 3/C

Tel.: +39 0424 511251 - Fax: +39 0424 37356
e-mail: infobassano@atag.it



SERVING INDUSTRY SINCE 1947