

# Flounder

This tool is especially suited to clean flat pipes and channels. The flat design combined with the rounded corners and edges provides the tool with ideal gliding properties.

Ceramic jets with flow straighteners and an optimized flow reversal create compact and aggressive water jets.

The low and compact design facilitates access to a wide variety of pipes and channels.

## Applications

- Appropriate for removing mud and loose debris in flat pipes and channels, i.e. run-off gutters



Flounder


Flounder 1/2" - 1 1/4"



70.050



1/2  
6 - 10  
16  
S1: 2 × M8, S2: 2 × M8  
S1: 15°, S2: 7.5°  
\*  
7.7 × 3.5 × 1.4  
5.78  
3,625  
✓



70.075


3/4  
8 - 16  
26  
S1: 2 × M8, S2: 4 × M8  
S1: 10°, S2: 0°  
\*  
7.7 × 3.9 × 2.0  
7.11  
3,625  
✓



70.100



1  
12 - 24  
53  
S1: 2 × M10, S2: 2 × M10, S3: 4 × M10  
S1: 15°, S2: 7.5°, S3: 0°  
\*  
13.4 × 6.3 × 2.2  
27.35  
3,625  
✓



70.125

1 1/4  
16 - 31  
66  
S1: 2 × M10, S2: 4 × M10, S3: 4 × M10  
S1: 15°, S2: 7.5°, S3: 0°  
\*  
15.0 × 7.1 × 2.8  
42.22  
3,625  
✓

|  |                                    |  |                    |  |                        |
|--|------------------------------------|--|--------------------|--|------------------------|
|  | Connecting thread [inch]           |  | Thrust jet         |  | Weight [lb.]           |
|  | Application range [inch]           |  | Front jet          |  | Recycling              |
|  | min. gpm at 1450 psi at the nozzle |  | Jet angle backward |  | Maximum pressure [psi] |

